

NanoSeal GT

Tile Sealer

Maintenance

Procedures

Application of NanoSeal GT varies greatly by substrate and contractor. The type substrate, the amount of product applied to the substrate will impact maintenance requirements. This document will guide the reader through general maintenance practices and does not address any post-application finishing that may require specific care.

Spills

Wipe up all spills immediately with a damp cloth. Continue until surface is clean and dry.

Cleaning

Dust mop regularly to maintain a dust-free, slip-resistant surface. Clean regularly using a new/clean microfibre mop with a 1:32 – 1:48 dilution of **NeutraClean GT** concentrate (refer to instructions on packaging). It is not recommended to use any means of automatic scrubber.

⚠ **Never use abrasive pads or hard-bristle brushes.**

⚠ **Never use acidic cleaners or strippers.**

Other PH neutral cleaners may be acceptable but not as effective at lifting contamination.

Small Localized Scratches

For small scratches, polish out with a white pad and then wipe clean.

⚠ **Do not use soaps or detergents as this may damage the topcoat of NanoSeal GT.**

Let the localized area dry and then apply a thin coat of NanoSeal GT as per the application instructions.

Large Scratches

For large scratches, polish out the entire area with a white pad and then wipe clean.

⚠ **Do not use soaps or detergents as this may damage the topcoat of NanoSeal GT.**

Let the area dry and then apply a thin coat of NanoSeal GT to the entire surface area as per the application instructions.

Scratch Prevention

Use walk-off mats in inclement weather.

⚠ **Do not leave wet mats or other fabrics on surface for extended periods of time.**

Use felt pads on furniture bases. Use chair mats for all types of chairs.

Deep Gouges

If gouging or other damage has occurred to the tile substrate, wipe the local area clean as above. Once dry, spot retouch the damaged area with NanoSeal GT to prevent dirt and contamination from passing to the tile substrate. Contact installer of substrate manufacturer for repair.

Warranty

Subject to Geon Tile Ltd. limited warranty. For copies and further information, visit geontile.com or contact Geon Tile.